ORIGINAL

0000089021

From: Orange Grove Water Company

P.O. Box 889

Yuma, Arizona 85366

Date: September 30, 2008

To: Docket Control

Arizona Corporation Commission 1200 West Washington Street Phoenix, Arizona 85007

Re: Cross-Connection Tariff

Docket No. W-02237A-08-0455

RECEIVED

2018 SEP 30 P 3: 37

AT OF PROPERTIONS
BUGGET CONTROL

Attached is an application by Orange Grove Water Company for approval of a Cross-Connection Tariff. The purpose of this tariff is to protect Orange Grove Water Company's water from the possibility of contamination caused by the backflow of contaminants that may be present on the customer's premises.

Thomas J. Bourassa, CPA

Representative

For Kathleen Day, President Orange Grove Water Company

Arizona Comparition Commission

DOCKETED

SEP 3 0 2008

DOC'TED AL

Company Name: Orange Grove Water Company Page 1 of 2

Docket No.: W-02237A-08-0455

CROSS-CONNECTION OR BACKFLOW TARIFF

| | CROSS-CONNECTION ON BACKFEOW TAKET |
|-------------|---|
| | |
| PURPOSE | |
| Th | e purpose of this tariff is to protect Orange Grove Water Company |
| requiring t | ("Company") water from the possibility of contamination the backflow of contaminants that may be present on the customer's premises by the installation and periodic testing of backflow-prevention assemblies pursuant to the of the Arizona Administrative Code ("A.A.C".) R14-2-405.B.6 and A.A.C. |
| REQUIRE | EMENTS: |
| and the A | compliance with the Rules of the Arizona Corporation Commission ("Commission") rizona Department of Environmental Quality ("ADEQ"), specifically A.A.C. R14-2-nd A.A.C. R18-4-115 relating to backflow prevention: |
| 1. | The Company may require a customer to pay for and to have installed a backflow-prevention assembly if A.A.C. R18-4-115.B or C applies. |
| 2. | A backflow-prevention assembly required to be installed by the customer under Paragraph 1 of this tariff shall comply with the requirements set forth in A.A.C. R18-4-115.D and E. |
| 3. | Subject to the provisions of A.A.C. R14-2-407 and 410, and in accordance with Paragraphs 1 and 7 of this tariff, the Company may terminate service or may deny service to a customer who fails to install a backflow-prevention assembly as required by this tariff |
| 4. | The Company shall give any existing customer who is required to install a backflow-prevention assembly written notice of said requirement. If A.A.C. R14-2-410.B.1.a. is not applicable, the customer shall be given thirty (30) days from the time such written notice is received in which to comply with this notice. If the customer can show good cause as to why he cannot install the device within thirty (30) days, the Company or Commission Staff may suspend this requirement for a reasonable period of time. |

FOR OFFICIAL USE ONLY

| Effective | Date: | | |
|-----------|-------|--|--|
| | | | |

| Company | y Name: | Orange Grove Water Company | Page | 2 o | of 2 |
|---------|---------|----------------------------|------|-----|------|
|---------|---------|----------------------------|------|-----|------|

Docket No.: W-02237A-08-0455

5. Testing shall be in conformance with the requirements of A.A.C. R18-4-115.F. The Company may require the customer to pay to have the backflow-prevention assembly tested as long as the Company does not require an unreasonable number of tests.

- 6. The customer shall provide the Company with records of installation and testing. For each backflow-prevention assembly, these records shall include:
 - a. assembly identification number and description;
 - b. location
 - c. date(s) of test(s);
 - d. description of repairs and recommendations for repairs made by tester; and
 - e. the tester's name and certificate number.
- 7. In the event the backflow-prevention assembly does not function properly or fails any test, and an obvious hazard as contemplated under A.A.C. R14-2-410.B.l.a. exists, the Company may terminate service immediately and without notice. The backflow-prevention assembly shall be repaired or replaced by the customer and retested.
- 8. In the event the backflow-prevention assembly does not function properly or fails any test, or in the event that a customer fails to comply with the testing requirement, and A.A.C. R14-2-410.B.1.a. is **not** applicable, the backflow-prevention assembly shall be repaired or replaced within fourteen (14) days of the initial discovery of the deficiency in the assembly or its function. Failure to remedy the deficiency or dysfunction of the assembly, or failure to retest, shall be grounds for termination of water service in accordance with A.A.C. R14-2-410.

| **FOR OFFICIAL USE ONLY* | **FOR | OFFI | CIAL. | LISE | ONI | V** |
|--------------------------|-------|------|-------|------|-----|-----|
|--------------------------|-------|------|-------|------|-----|-----|

| Effective | Data | | |
|-----------|---------|--|--|
| errecuve. | i jaie: | | |